

**Note:** These motors differ from Brushless 'Modified' motors.

Motors on this list have to comply with BRCA Electric Board Rules, Section 10.

All motors detailed below, must be (or previously have been) available for purchase at retail outlets throughout the UK.

Motor Builder	Type/Range	Illustration only	Distributor	Notes	Approval Date
WAVE	WAVE Linear Pt.# TW2001-105		MuchMore	Sensored system. "Y" Wind. Black Aluminium End-Plates with SP etched under label. Black stator sleeve with 10.5T etched. Black sintered rotor, 12.3 dia, 7.22 core. Rotor with one balancing ring.	16.03.09
GM	Brushless PRO. Pt.# 97290		Schumacher	Sensored system. "Y" Wind. Dark Gun-Metal Aluminium End-Plates, GM-Racing etched. Dark Gun-Metal stator sleeve with S10.5T & Pt.# etched. Black sintered rotor, 12.3 dia, 7.22 core. Rotor with one balancing ring.	02.03.09
Tekin	Tekin Redline 10.5T Spec. Pt. # TT2253 (Etched Can)		MuchMore	Sensored system. "Y" Wind. Red Aluminium mounting plate. Black moulded End-Bell with Tekin. Grooved Al. bonded stator sleeve with 10.5T etched. Nickle plated sintered rotor, 12.5 dia, 7.26 core. No balance rings.	15.12.08
Speed Passion	Speed Passion Stock Pt. # SPF105		Schumacher	Sensored system. "Y" Wind. Black Aluminium End-Plates with SP 10.5T. Black stator sleeve with 10.5T engraved. Black sintered rotor, 12.3 dia, 7.25 core. Rotor with one balancing ring.	08.09.08
LRP	Vector X11 Stock Spec. Pt. # 50830		SMD	Sensored system. "Y" Wind. Black moulded End-Bell with XTEC. Blue anodised ring. Chamfered mounting face. Sleeve etched "10.5 Turns". Sintered rotor, 12.3 dia, 7.35 core. Rotor shaft, Black. Manufacturers 'slotted' End Plates (std. & thin versions) allowed at pinion end. Manufacturers later 'grooved' Al. End Plate with name engraved allowed at terminal end.	09.06.08 19.07.08
Novak	SS Pro. Pt. # 3410		CML	Sensored system. "Y" Wind. Black moulded End-Bell with NOVAK. Blue plastic ring. Mounting face with or without chamfer. Stator marked "10.5 Turns". Nickel Pt. Sintered rotor, 12.3 dia, 7.25 core. Rotor shaft with plain bevel at pinion end.	14.04.08 28.04.08
Nosram	Spec.' Storm Evolution Pt. # 91830		Mirage	Sensored system. "Y" Wind. Black moulded End-Bell with XTEC. Blue anodised ring. Chamfered mounting face. Sleeve etched "10.5 Turns". Sintered rotor, 12.3 dia, 7.35 core. Rotor shaft, Black. Manufacturers 'slotted' End Plates (std. & thin versions) allowed at pinion end. Manufacturers later 'grooved' Al. End Plate with name engraved allowed at terminal end.	07.04.08. 19.07.08.

Paul Worsley. (BRCA Electric Board Tech. Officer) 16.03.09.

E-Mail paul.worsley@virgin.net